

HWN-4100MH-P(B) SERIES NVR

Key Feature

- Up to 4/8-ch IP camera input (up to 8 MP)
- Up to 40/80 Mbps incoming bandwidth, and 80 Mbps outgoing bandwidth
- Support H.265+/H.265/H.264+/H.264 video compression
- HDMI and VGA independent output for HWN-4108MH-8P(B)



Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%

Storage and Playback

- 1 SATA interface (up to 6 TB capacity per HDD)
- Smart search for efficient playback

Smart Function

- Support multiple VCA (Video Content Analytics) events

Network & Ethernet Access

- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- 1 self-adaptive 10/100 Mbps network interface




Specification

Model	HWN-4104MH-4P(B)	HWN-4108MH-8P(B)
Video and Audio		
IP video input	4-ch	8-ch
	Up to 8 MP resolution	
Incoming/outgoing bandwidth	40 Mbps/80 Mbps	80 Mbps/80 Mbps
HDMI output	4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA simultaneous output	4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA independent output
VGA output	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA simultaneous output	1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA independent output
Audio output	1-ch, RCA (Linear, 1 K Ω)	
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 k Ω)	
Decoding		
Decoding format	H.265/H.265+/H.264/H.264+/MPEG4	
Video resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF	
Synchronous playback	4-ch	8-ch
Capability	1-ch @ 8 MP / 4-ch @ 1080p	
Stream type	Video, Video & Audio	
Network		
Remote connection	16	64
Network protocol	IPv6, HTTPS, UPnP, NTP, SADP, SMTP, PPPoE, DDNS, iSCSI, NFS	
Network interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface	
Recording resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF	
Interoperability	ONVIF 2.2	
Camera protocol	HIKVISION, ACTi, ARECONT, AXIS, BOSCH, BRICKCOM, CANON, HUNT, ONVIF (Version 2.5), PANASONIC, PELCO, RTSP, SAMSUNG, SONY, VIVOTEK, ZAVIO	
PoE		
Interface	4, RJ-45 10/100 Mbps self-adaptive Ethernet interface	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤ 50W	≤ 75W
Supported standard	IEEE 802.3 af/at	
Auxiliary Interface		
SATA	1 SATA interface	
Capacity	Up to 6 TB capacity for each disk	
USB interface	Rear Panel: 2 × USB 2.0	
General		


Power supply	48 VDC, ≤ 65 W	48 VDC, ≤ 90 W
Consumption (without HDD)	≤ 10 W (without enabling PoE)	
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)	-10 °C to 45 °C (14 °F to 113 °F)
Working humidity	10% to 90%	
Dimension (W × D × H)	260 × 223 × 48 mm (10.2" × 8.8" × 1.9")	
Weight (without HDD)	≤ 1 kg (2.2 lb)	
Certification		
CE	EN 55032:2015; EN 50130-4:2011+A1:2014; EN 61000-3-2:2014; EN 61000-3-3:2013	
FCC	FCC Part15 sub B; ANSI C63.4	

Dimension



scale/1:1;Unit/mm

Physical Interface



No.	Description	No.	Description
1	48 VDC Power Supply	6	USB 2.0 Interface
2	AUDIO OUT	7	LAN Network Interface
3	AUDIO IN	8	Network Interfaces with PoE function (4 interfaces for NVR-104MH-C/4P(B) and 8 interfaces for NVR-108MH-C/8P(B))
4	VGA Interface	9	GND
5	HDMI Interface		

Available Model

HWN-4104MH-4P(B), HWN-4108MH-8P(B)

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com